

# Sertifikaat

REPUBLIEK VAN SUID AFRIKA

PATENT KANTOOR DEPARTEMENT VAN HANDEL **EN NYWERHEID** 

**897 2004/00082** 

1 2 OCT 2004

Certificate

REPUBLIC OF SOUTH FRICA

PATENT OFFICE DEPARTMENT OF TRADE AND **INDUSTRY** 

Hiermee word gesertifiseer dat This is to certify that

RTM 2004/00082 REC'D 0 2 DEET 2004 **WIPO** PCT

the documents annexed hereto are true copies of:

Application forms P.1 and P.3, provisional specification and drawings of South African Patent Application No. 2003/6145 as originally filed in the Republic of South Africa on 8 August 2003 in the name of Jan Petrus Human for an invention entitled: " Mould and moulding apparatus ".

Geteken te

Signed at

**PRETORIA** 

in die Republiek van Suid-Afrika, hierdie


in the Republic of South Africa, this

22

dag van September 2004

day of

Registrar of Patents



SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH **RULE 17.1(a) OR (b)** 

[Section 30 (1)—Regulation 22]

APPLICATION FOR A PATENT AND ACKNOWLER

•	(See no	otes overlear)	# M 8 E M 1				
The grant of a patent is hereby and duplicate.	requested by the under	mentioned applican	FOLL WATER TO SEE THE MEDITION OF THE HANDELS WERE AND SEE THE MEDITION OF THE HANDELS WERE TO SEE THE MEDITION OF THE HANDELS WERE THE MEDITION OF THE MEDITION OF THE HANDELS WERE THE MEDITION OF T				
Official Application No. 2 0 0 3 /	6 1 4 5	Applica	nt's or agent's reference				
21 01							
(ii)							
71 Full name(s) of applicant(s)		HUMAN JAN PE	TRUS				
(iii)							
Address(es) of applicant(s) 15 LOBELIASTRAAT SOMERSET-WES 7130							
(iv)	l						
Title of invention MOULD At	ND MOULDING APPARA	TUS					
(v)	•		•				
The applicant claims priority as se	t out on the accompanying	g form P 2.					
(vi)							
This application is for a patent of a	addition to Patient Applicat	ion No.					
21 01							
(vii)							
This application is a fresh application	ion in terms of section 37 a	and based on Application	No.				
21 01			•				
(viii)		•					
This application is accompanied by			_				
	onal or two copies of a con	nplete specification of	pages.				
	2. Drawings of						
	d abstract (form P 8 in dup						
	4. A copy of Figureof drawings (if any) for the abstract.						
	5. An assignment of Invention.						
	6. Certified priority document(s) (state number).						
7. Translation of the priority document(s).							
An assignment of priority rights.  9. A copy of the form P 2 and the specification of S A. Ratent Application No. 21 01							
9. A copy of the form P 2 and the specification of S.A. Patent Application No. 21 01  10. A declaration and Power of Attorney on form P 3.							
12. Request for classification			`				
13.	on on on						
(ix) D p	R	1					
4 Address for service: P.O. BO		ASSOCIATES					
		127					
	day of AUGUST  Signature of applicant(s	2003 ) or agent	REGISTRAR OF PARTNERS DESIGNS, TRADE MARKS AND COPYRIGHT Official date stamp  2003 - 08- 08				

#### REPUBLIC OF SOUTH AFRICA PATENTS ACT, 1978 DECLARATION AND POWER OF ATTORNEY

(Section 30 - Regulation 8, 22(i)(c) and 33)

ATENT APPLICATION NO	REF:		LODGING DATE	
01 2003/6145		•	22	2003 -08- 0 8
ULL NAME(S) OF APPLICANT(S)				
! HUMAN JAN PETRUS				
ULL NAME(S) OF INVENTOR(S)	1			
! HUMAN JAN PETRUS	•	. ·		
		I		
ARLIEST PRIORITY CLAIMED	COUNTRY	NUMBER	DA	re
	33.	31	32	
TE: The country must be indicated by its Interna	tional Abbreviation - see	schedule 4 of the Regulatio	ns	
ITLE OF INVENTION			•	
MOULD AND MOULDING A	APPARATUS			

HUMAN JAN PETRUS I/\<del>∀e</del>

hereby declare that :-

- 1. I/we am/are the applicant(s) mentioned above;
- I/we have been authorized by the applicant(s) to make this declaration and have knowledge of the facts herein 2. of the applicant(s); stated in the capacity of
- the inventor(s) of the abovementioned invention is/are the person(s) named above and the applicant(s) has/have acquired the right to apply by virtue of an assignment from the inventor(s);
- to the best of my/our knowledge and belief, if a patent is granted on the application, there will be no lawful 4. ground for the revocation of the patent;
- this is a convention application and the earliest application from which priority is claimed as set out above is the 5. first application in a convention country in respect of the invention claimed in any of the claims; and
- , patent attorneys, are authorised, jointly and severally, 6. the partners and qualified staff of the firm of with powers of substitution and revocation, to represent the applicant(s) in this application and to be the address for service of the applicant(s) while the application is pending and after a patent has been granted on the application.

SIGNED AT SOMERSET-WES

TH DAY OF THIS

AUGUST

2003

SIGNATURE(S) (no legalization necessary)

In the case of application in the name of a company, partnership or firm, give full names of signatory/signatories, delete paragraph 1, and enter capacity of each signatory in paragraph 2.

If the applicant is a natural person, delete paragraph 2.

If the right to apply is not by virtue of an assignment from the inventor(s), delete "an assignment from the inventor(s)" and give details of acquisition of right. For non-convention applications, delete paragraph 5.

# BEST AVAILABLE COPY

# REPUBLIC OF SOUTH AFRICA PATENTS ACT, 1978

## PROVISIONAL SPECIFICATION

(Section 30(1) - Regulation 27)

Official Application No.	Lodging Date
21 21 . 2003/6145	22 <b>2003 -08- 0 8</b>
	ገ ·
Full name(s) of applicant(s)	<u> </u>
71 HUMAN JAN PETRUS	
	¬ ·
Full name(s) of inventors(s)	
72 HUMAN JAN PETRUS	
Title of invention	

MOULD AND MOULDING APPARATUS

#### FIELD OF THE INVENTION

This invention relates to the production of moulded articles and the apparatus such as injection moulding, compression moulding for producing moulded articles such as closures.

# **BACKGROUND OF THE INVENTION**

Different techniques are in commercial use and by means of which articles such as closures and preformed bottles are manufactured using synthetic plastic materials.

Injection moulding is the most commonly used this method comprise two mould parts pressed into a shutoff position, molten synthetic plastic material is forced through a small hole to take up the shape of the space between the two mould parts.

Compression moulding comprises a rotating carousel on which female moulds are mounted, whilst the carousel is rotating a pellet of molten synthetic plastic material is displaced from a extruding device into the female mould, a male mould comprising shutoff means is pressed onto the female mould and the core eventually shapes the article. This technique is used for the production of closures where high production volumes are required. There are certain limitations insofar moulding specific articles such as closures with undercut e.g. scoring line, slits, gaps and holes in the article.

# BRIEF DESCRIPTION OF THE INVENTION

According to one aspect of the present invention there is provided a mould comprising a female mould which include at least one plunger which reciprocate inside the bore of the said female mould, means for displacing mouldable material into said female mould, a male core pressed onto the female mould, said plunger being forced forward with mechanical means, urging the said mouldable material to take up shape of the defined space between the mould parts.

REGISTRAR OF PATENTS DESIGNS, TRADE MARKS AND COPYRIGHT

2003 -08- 08

REGISTRATEUR VAN PATENTE, MODELLE, HANDELSMERKE EN OUTEURSREG Said moulding technique, comprise the means to first shutoff mould sets, which include protrusions inside the defined space to make undercuts e.g. slits, gaps or holes in articles such as closures.

In our South African patent application filed 30 July 2003 we disclosed a mould and method of moulding comprising a female mould which reciprocate on at least one shaft which can be attached at one end, means for displacing mouldable material into said female mould, a male mould forced onto the female mould, urging the said material to take up shape of the space between the two mould parts.

The disclosure of the specifications of the South African patent application filed 30 July 2003 is hereby incorporated into the disclosure of the present specification.

#### BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the present invention, and to show how the same may be carried into effect, reference will now be made, by way of example, to the accompanying drawings in which:-

Figure 1 is an isometric view of an open male and female mould.

Figure 2 is a front view of a male and female mould, the female mould comprise a reciprocating plunger.

Figure 3 is a front view of a male and female mould closed.

Figure 4 is a front view of a male and female mould closed showing the moulded product.

## DETAILED DESCRIPTION OF THE DRAWINGS

Figure 1 shows the recess 13 of the female mould 12 and the cavity 14 where the core 10.1 of the male mould 10 engages.

Figure 2 is the said male mould 10 and female mould 12 open, which receives mouldable material 11. The female mould 12 is attached at the end 20 onto a


moulding device not shown. The female mould 12 comprises a bore 21 which guide a reciprocating plunger 17 during the moulding process.

Figure 3 is the male mould 10 and the female mould 12 closed. The male mould 10 comprises a treaded core 10.1 which fits into the female cavity 14; the shutoff space between the walls of the female cavity 14 and the core 10.1 defines the shape of the cap 18 as described in Figure 4.


Figure 4 is the said closed moulds 10 and 12; the shaft 17 is forced towards the end 22 of the bore 21 with mechanical means forming the cap 18. Mechanical means can comprise methods such as hydraulics used on injection moulding and a rotating carousel comprising a cam system used on compression moulding.


This method of moulding mouldable material inside the mould can also produce articles such as a preform without an injection point.


The said moulds and method of moulding inside the moulds can be fitted to any known moulding machine using their operating means to produce articles.



FIGI










FIG4

REST AVAILABLE COPY